OP100

PLENUM FOR WALL GRILLES



VARIANTS

OP100T, OP100A, OP100S

The OP100 plenum box is suitable for connection of rectangular wall grilles. Unlike the ceiling plenum DP100, the OP100 has no protruding clinched ribs. Instead, the sides are folded over to keep it as compact as possible. It's available in three executions: Side entry, top entry or asymmetric top entry. Flow control is possible by means of a perforated damper in the inlet spigot.

No protruding clinched ribs

Folded over sides to keep it as compact as possible

Also available with asymmetric top entry










TECHNICAL INFORMATION

APPLICATION	Туре	Plenum for wall grilles	
	Version	Side / Top / Top asymmetrisch	
CONSTRUCTION	Shape	Rectangle	
	Length	100-2000mm	
	Height	38-900mm	
	Depth	100-650mm	
	Spigot	Ø80-400mm	
	OP100	For mounting of wall grilles in combination with mounting frame GR001	
	OP101	Equipped with folded lip for direct mounting of wall grilles with clip fixing	
PLENUM	Material	Galvanised (275g/m²) sheet steel, PP/TPE spigot	
	Insulation (optional)	Melamine 6mm	
	Spigot plenum	Class D spigot with double lip seal	
	Volume control	Perforated volume control disk with manual operation (optional)	
	Mounting options	Mounting straps available upon request	
PLENUM	Spigot OP100 OP101 Material Insulation (optional) Spigot plenum Volume control	Ø80-400mm For mounting of wall grilles in combination with mounting frame GR001 Equipped with folded lip for direct mounting of wall grilles with clip fixing Galvanised (275g/m²) sheet steel, PP/TPE spigot Melamine 6mm Class D spigot with double lip seal Perforated volume control disk with manual operation (optional) Mounting straps available upon	

PRODUCT KEY



1: Equipped with folded lip for direct mounting of wall grilles with clip fixing

2: Equipped with folded lip for direct mounting of wall grilles with concealed screw fixing


DIMENSIONS


ØN	D2	E	H1
80	D - 51	52	101
100	D - 61	52	121
125	D - 83	58	165
160	D - 100	58	200
200	D - 120	58	240
250	D - 145	58	290
315	D - 169	49	338
355	D - 189	49	378
400	D - 212	49	423

D1 = 50, 75, 100, 125, of 150


All dimensions in mm


OP100-T-D1 OP100







OP101-T-D1







OP102-T-D1





OP100-A-D1





OP100-S-D1

